



PVA Glue

A GENERAL PURPOSE SOLVENT FREE ADHESIVE

Date: 30 March 2022

Fact Sheet No.: TDS02021

YOUR SMART ADVANTAGES

- Multi-purpose, solvent free white glue which dries clear
- Easy to use bottle with re-sealable cap
- UKCA & CE approved

USES

Bostik PVA Glue is a water-borne adhesive based on vinyl acetate homo-polymer & polyvinyl alcohol, supplied in an easy to use plastic bottle.

Bostik PVA Glue is a general purpose PVA Glue that dries clear making it suitable for most arts and crafts projects and ideal for scrapbooks, card making, modelling and school projects. Bostik PVA glue bonds to most materials, including paper, card, wood and fabric. You can even use it to make slime, create a glossy finish on projects or mix it with powder for finger painting. Bostik PVA glue has been formulated to be washable so accidental messes can easily be cleaned up.

Bostik PVA Glue has been designed to be UKCA and CE compliant making it ideal for both schools and home.

PRODUCT CHARACTERISTICS

Colour	White, dries clear/opalescent
Form	Liquid
Specific Gravity	1.00-1.10 g/cm ³
Composition	Vinyl acetate homo-polymer/ polyvinyl alcohol

Product Code	30613443 118ml bottle on blister x 6
Storage/Shelf Life	12 months in its original sealed packaging, stored above 5°C in a dry, cool, ventilated area out of direct sunlight. Avoid close proximity to strong acids, heat source and strong oxidising agents.
Odour	Odour-free

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	Above 15°C
Drying Times	Full cure on paper/Card in 12 hours. For wood full cure in 24 hours.

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik PVA Glue refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk

PREPARATION

1. Always open and use adhesive products over a protected work surface.
2. Ensure the surfaces to which Bostik PVA Glue is to be applied are clean and dry.

APPLICATION

3. Twist the blue part of the nozzle anti-clockwise.
4. Squeeze the bottle gently and apply the glue to one or both surfaces.

5. For non-porous surfaces, allow the glue to become tacky to the touch before bringing the surfaces together.
6. After use wipe the nozzle and turn the nozzle clockwise to stop glue drying out.

CLEANING

7. Any excess glue can be removed by using a damp cloth
8. Can be washed out of clothes using warm soapy water, ideally before glue is dry.

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik PVA Glue, available at www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	sds.box-eu@bostik.com